

8(3): 1-16, 2019; Article no.AFSJ.48388 ISSN: 2581-7752



J. Isa^{1*}, A. S. Oyerinde¹, K. A. Jimoh¹ and A. O. Jegede¹

¹Department of Agricultural Engineering, Federal University of Technology, Akure, Nigeria.

Authors' contributions

This work was carried out in collaboration among all authors. Author JI designed the study, performed the statistical analysis, wrote the protocol and wrote the first draft of the manuscript. Authors ASO and KAJ managed the analyses of the study. Author AOJ managed the literature searches. All authors read and approved the final manuscript.

Article Information

DOI: 10.9734/AFSJ/2019/v8i329991 <u>Editor(s)</u>: (1) Dr. Mindaugas Liaudanskas, Department of Pharmacognosy, Faculty of Pharmacy, Lithuanian University of Health Sciences, Lithuania. <u>Reviewers:</u> (1) Larissa De Sousa Satiro, State University of Paraíba, Brazil. (2) Dr. Rupali Sengupta, SNDT University, India. (3) Dr. Charles Apprey, Kwame Nkrumah University of Science and Technology, Ghana. Complete Peer review History: <u>http://www.sdiarticle3.com/review-history/48388</u>

Original Research Article

Received 25 January 2019 Accepted 05 April 2019 Published 17 April 2019

ABSTRACT

Introduction: The hydration of grains is a process that consists of soaking them in water in order to increase their moisture content and this is a crucial step in industrialized processing and provides several beneficial effects on their physicochemical and nutritional qualities.

Aims: This study focused on modeling of hydration characteristics of five varieties of cowpea which are: *Gombe*, *Oloyin* white, Drum, *Oloyin* brown and *Sokoto* cultivated in Nigeria.

Methodology: The experiments were carried out using electronic water bath at five temperatures (30, 40, 50, 60, and 70°C) in three replications. The amount of water absorption by five selected varieties of cowpea grains was calculated by measuring the increase in the mass of soaked grains per time. Five standard models of water absorption were fitted to the experimental data. Coefficient of determination (R^2), chi-square (x^2) and root mean square error (*RMSE*) were used to evaluate the models.

Results: The initial moisture content of the saturated cowpea was estimated as 13.56 ± 1.15 , 15.05 ± 2.27 , 13.30 ± 0.37 , 10.85 ± 0.13 , 12.40 ± 0.13 for *Gombe*, *Oloyin* white, Drum, *Oloyin* brown and *Sokoto* varieties respectively. The water uptake of the cowpea was faster at the initial stage and gradually slow down until the equilibrium moisture content was attained for all the varieties.



Conclusions: Weibull model was adjudged as the best fitted model for describing the water absorption property of all the varieties of the cowpea and the Activation energy of *Gombe, Oloyin* white, Drum, *Oloyin* brown and *Sokoto* varieties are 42.26 ± 4.65 , 40.36 ± 8.90 , 39.47 ± 8.62 , 43.08 ± 5.25 and 39.66 ± 6.72 respectively.

Keywords: Cowpea varieties; physical properties; hydration; thermodynamics; modelling.

1. INTRODUCTION

Cereals and legumes are potential ingredients for many processed foods due to their protein contents. Among these foods, cowpea (Vigna unguiculata L.) is an important plant food that is widely produced and consumed. This agricultural material is important source of carbohydrate, protein, iron, vitamin B and minerals. On dry weight basis, these seeds contain mostly proteins 17-28%, fats 3%, and carbohydrates 50-53%, ash 3% and fibre 6%, and it is also an important item in the diet of most people [1,2]. The possible contribution of dry beans to improving the lives of subsistence farmers and his family in Africa is obvious. The excellent flavour of the cooked seeds makes it superior to other pulses in Southern Nigeria [3]. It was remarked to be exceptionally nutritious by Rachie [4]. Different forms of local recipes are prepared from the crop to meet the dietary needs of the people. In most West African communities, the seed grains are boiled and eaten with other staples such as yam, plantain, cassava, corn/maize, etc. A popular snack is produced from the grains through roasting particularly in Enugu/Nsukka area of Nigeria. Owing to the presence of the ANFs in various quantities in dry beans (like other legumes), the consumption of the bean will require processing for safety as human meals [5]. Cooked seeds of dry beans have higher fibre content, high efficiency of protein digestibility, higher amino acid availability, high gross and metabolizable energy and good fatty acid profile [2].

The hydration of grains is a process that consists of soaking them in water in order to increase their moisture content. This is a crucial step in industrialized processing and provides several beneficial effects on their physicochemical and nutritional quality [6,7,8,9,10]. Soaking is widely used in processing different grains for many reasons, as hydration is necessary for processes like cooking, extraction, fermentation, germination and malting. The hydration of grains before cooking helps to soften the bean structure and so, reducing the cooking time [11]. This process promotes the activation of cell-wall

enzymes, decreases the degree of polymerization of rhamnogalacturonan and increases the solubility of poly galacturonan and galactan, which results in better polysaccharide solubility and shorter cooking time [12]. In addition, hydration enhances the homogeneous gelatinization of the starch and the homogeneous denaturation of proteins during cooking [13]. Therefore, a similar texture is obtained in the whole grain.

Moreover, the heat transfer through the grain during cooking is enhanced by the absorbed water, thus improving the inactivation of antinutritional factors [14] such as protease inhibitors, lectins, saponins, vicine, convicine, phytates. alkaloids. and indigestible oligosaccharides [15]. Hydration also improves component extraction from grains, which in this case is sometimes called the steeping process. The most commonly-extracted component from grains is starch, especially from cereal grains, and is conducted by wet milling. Softening the grains by hydration improves their wet grinding and so facilitates starch purification [16]. In addition, the hydration process is used to extract toxic components from beans. For instance, the Andean lupin (Lupinus mutabilis Sweet) has a high level of toxic alkaloids (lupanine), which needs to be extracted before being consumed. This extraction is performed in water; thus, the grains need to be hydrated [17]. In addition, during the hydration process, some antinutritional compounds, such as phytic acid, tannins, phenols, α-amylase, and trypsin inhibitors, are extracted [18].

The grain hydration process is mainly a mass transfer unit operation, in which the water activity difference acts as the driving force. In other words, the water is transported from a substance with a high effective water concentration (soaking water) to a substance with a low effective water concentration (grain), a phenomenon called diffusion. In addition, the complex structure and different tissues and cells of the grains form channels of many sizes, structure, composition, zones with varied permeability through which the water can flow. Therefore, the water does not only enter the grains by diffusion, but also by capillary flow. Thus, the hydration process is not as simple as it seems and involves not only mass transfer mechanisms, but also those of fluid flow. Consequently, the hydration process is of significant importance in the industrialization of grains. However, this step is a batch process, which can take many hours and uses a substantial quantity of water. For that reason, its study, description and optimization are very desirable [19].

The water uptake of the grains can show two forms of behaviour, which are differentiated by the mass transfer rate at the beginning of the process. In the downward concave shape (DCS) behaviour, the water influx rate is a maximum at the beginning of the process and falling to zero after enough time has elapsed at the product equilibrium moisture content (Meg). Among many models, the Peleg Model [20] is the most widely used equation to describe this behaviour. The sigmoidal behaviour is described by an initial lag phase, i.e., an initial phase with a low water uptake rate. In this case, the water influx rate firstly increases, until an inflexion point is reached. After which the rate decreases to zero when the product reaches its equilibrium moisture content (Meg). This behaviour can be described by the Kaptso et al. model. The sigmoidal behaviour is of higher interest, since it is the lag phase that slows the process. All the grains that presented this behaviour are from Leguminosae or Fabacea family, like cow-pea [2], common bean [21], lima bean [22], Adzuki beans [23] and Andean lupin beans [15].

Many studies have reported the influence of temperature on water absorption property which includes soybean, amaranth grain and maize kernel [24,25,26] and many other grains. However, effect of varietal variations and processing variable on the rate of water uptake and moisture absorption property of cowpea grown in Nigeria, and it processed form have not been fully and thoroughly established. The aim of this work is to study the hydration behavior of cowpea as influenced by varieties and temperature.

2. MATERIALS AND METHODS

2.1 Sample Collection

The five varieties of cowpea grains were obtained from a local market in Akure, Southwest Nigeria. The material was cleaned to remove

foreign materials such as stones, broken grains, weevil damaged grains and dirt, sealed in an airtight container and kept in cool and dry place prior to its usage. Other material used for the study of water absorption characteristics include; Electronic Water bath, Beakers, measuring cylinder, weighing balance, venier callipers, distil water, Sample holder, Blotting paper, Hand towel.

2.2 Initial Moisture Content Determination

The initial moisture content of the seeds was determined using the oven dry method, the sample was placed in the laboratory oven at 105±1°C for about 24 h in hot air oven. Average moisture content was subsequently calculated on a percentage dry basis (% d.b) as shown in equation 1

$$Mc = \frac{M_W - M_d}{M_d} X \ 100 \tag{1}$$

Where Mc is moisture content on dry basis (%), M_w is mass of wet sample (g) and M_d is the mass of dry sample (g).

2.3 Determination of Physical Properties of Grains

The physical characteristics of the cowpea seeds were evaluated according to Baryeh [27]. 100 randomly selected seeds were used to measure length (L), width (W) thickness (T), from the three principal dimensions which are in the three mutually perpendicular directions using a vernier caliper and the mass (M) of the seeds was measured using digital weighing balance. Using the readings, the geometric mean diameter (Dm), arithmetic mean diameter (Da)sphericity (ϕ), surface area (A), volume (V)and mass (ρ) was calculated using the relationship shown in the equation 1-8 respectively;

$$D_m = \sqrt[3]{(LWT)} \tag{2}$$

$$D_a = \frac{L+W+T}{3} \tag{3}$$

$$\varphi = \frac{(LWT)^{1}/_{3}}{L}$$
(5)

$$A = \pi D_m^2 \tag{6}$$

$$V = \frac{\pi.WT.L^2}{6[2L - (WT)^{0.5}]}$$
(7)

$$\rho = \frac{M}{V} \tag{8}$$

2.4 Soaking Experiment

The moisture content change of the cowpea grains during soaking in water were measured at five different water temperatures (30, 40, 50 60, and 70°C) for five different varieties of cowpea; *Gombe, Oloyin* white, Drum, *Oloyin* brown and *Sokoto* varieties. Beakers (200 ml) containing 120 ml of distilled water were placed in thermostatically-controlled water baths (WBH 14-420 PEC MEDICAL USA) at the predetermined temperatures. Three replicates of 20±0.5 g samples were weighed into the beakers giving a volumetric water-grain ratio of 5:1.

Throughout the soaking period, the samples were fully immersed in water and removed from the water bath after 15 minutes. The soaked samples were drained and transferred to a filter cloth and blotted carefully to remove excess surface water [28,29]. The weight of the samples was then determined using a digital balance (A & D Co. Ltd., 14000176, Japan). The procedure was repeated at intervals of 15 minutes for first hour. 30min interval for the second hour and 60 min interval until equilibrium is attained to obtain the water absorption data, the experiments were terminated when the incremental change in sample weight was less than 0.05 g when measured after 1 hr of soaking, or up to a total soaking time of 10 hrs. The increase in sample mass during soaking in water was considered to be an increase in sample moisture content [30].

2.5 Modeling of Absorption Characteristics

For fitting the moisture uptake of soaked five varieties of cowpea, five models were used to estimate the parameters associated with each model. The list of the empirical models and the respective equations used in this study is presented in Table 1. The best fitted model was determined based on the highest coefficient of determination (R²) and the lowest values of the root mean square error (RMSE) and chi-square (χ^2) between the predicted and experimental results (COX et al., 2012). The standard error of estimate (SEE) indicates the fitting ability of a model to a set of data and represents the deviation of the dependent variable Mt,

$$SEE = \sqrt{\sum_{i=1}^{n} \frac{(M_{\exp,i} - M_{\text{prep},i})^2}{d_f}}$$
(5)

$$X^{2} = \sum_{i=1}^{N} \frac{(M_{\exp,i} - M_{\operatorname{prep},i})^{2}}{N-n}$$
(7)

$$R^{2} = \sum_{i=1}^{n} \frac{(M_{exp,i} - M_{exp,ave})^{2} - \sum_{i=1}^{n} (M_{exp,i} - M_{pre,i})^{2}}{\sum_{i}^{n} (M_{exp,i} - M_{exp,ave})^{2}}$$
(8)

RMSE =
$$\sqrt{\frac{1}{N} \sum_{i=1}^{N} (M_{\text{pre},i} - M_{\text{exp},i})^2}$$
 (9)

Where, $M_{exp,i}$ is the *i*th experimentally observed moisture content (%d.b), $M_{pre,i}$ the *i*th predicted moisture content (%d.b), $M_{exp,ave}$ is average moisture content observed (d. b. %), N is the number of data, d_f is degree of freedom and *n* is the number of the constant coefficient of model.

MR is the rate of moisture uptake, and is given by the equation: $MR = \frac{M_{o-M_{f}}}{M_{o-M_{o}}}$

 M_o is the initial moisture content of the bean, M_t is the moisture content of bean at time t, and M_e is the final moisture content at equilibrium.t is the hydration duration (in min), and the variables k_1 , k_2 , k, τ , α and β are the coefficients of the empirical models which was solve using nonlinear regression analysis on Microsoft excel version 2016 microsoft.inc.

Model	Equation	Reference	
First Order	$\frac{m_{t-m_{\infty}}}{m_{o-m_{\infty}}} = \exp\left(-K.t\right)$	[31]	
Peleg	$M_t = M_o + \frac{t}{K_1 + K_2}$	[20]	
Page	$\frac{m_t - m_\infty}{m_o - m_\infty} = \exp\left(-\text{Kt}\right)$	[32]	
Weibull	$\frac{M_t}{M_{\infty}} = 1 - \exp\left(-\left(\frac{t}{\beta}\right)^{\alpha}\right)$	[33]	
Kaptso	$M_t = \frac{M_{\infty}}{1 + \exp[-Kt] \cdot (t - \tau)}$	[2]	

Table 1. Models used to describe the moisture uptake by soaking

3. RESULTS AND DISCUSSION

3.1 Physical Properties

Table 2 shows the initial moisture content of five selected varieties of cowpea and there corresponding physical appearance. The initial moisture content estimated using standard oven dry method as 13.56 ± 1.15 , 15.05 ± 2.27 , 13.30 ± 0.37 , 10.85 ± 0.13 and 12.40 ± 0.13 for *Gombe, Oloyin* white, Drum, *Oloyin* brown and *Sokoto* varieties respectively.

Table3 shows the summary statistic of the physical properties of the different varieties of cowpea; *Gombe*, Drum, *Sokoto*, *Oloyin* white, and *Oloyin* brown. The weight of the seed was measured as 0.19 ± 0.04 , 0.30 ± 0.07 , 0.34 ± 0.05 , 0.25 ± 0.04 and 0.25 ± 0.04 g for *Gombe*, Drum, *Sokoto*, *Oloyin* white, and *Oloyin* brown respectively. The highest mass was recorded in the *Sokoto* variety and lowest wat recorded in the *Gombe* variety. The seed mass of cowpea

obtained in the present study fall within the same range (0.10-0.24 g) reported by Olapade [34] for eight varieties of Nigerian cowpeas and less than the seed weight of bambara (0.50-0.80 g) obtained by Baryeh [35]. The length (L), width (W) and thickness (T) shown Table 3 for all the selected varieties of cowpea are 0.89 ± 0.11, 0.70 ± 0.07 and 0.58 ± 0.08 respectively for Gombe variety, 1.15 ± 0.10, 0.82 ± 0.09 and 0.61 \pm 0.07 for Drum variety respectively, 1.15 \pm 0.14, 0.8 ± 0.15 and 0.68 ± 0.07 for Sokoto variety respectively, 1.02 ± 0.21 , 0.75 ± 0.10 and $0.60 \pm$ 0.06 for Oloyin white variety respectively and 1.12 ± 0.12 , 0.81 ± 0.10 and 0.56 ± 0.06 for Olovin brown respectively. This result is lesser than the findings of [34] who reported on cowpea seeds the range values of L, W and T, to be 0.73-1.00 cm, 0.49-0.73 cm and 0.33-0.57 cm, respectively and in tandem with the corresponding range values reported by Barveh [35] on bambara seeds were 1.01–1.52 cm. 0.95–1.15 cm and 0.82–1.10 cm. respectively.

Table 2. Initial moisture content of the selected varieties of cowpea

Varieties	Mean	SD	Coat colour	Eye colour
Gombe	13.56168	1.151601	white	White
<i>Oloyin</i> white	15.04894	2.268778	White	White
Drum	13.29697	0.371018	Darkish brown	brown
<i>Oloyin</i> brown	10.84599	0.125566	Brown	white
Sokoto	12.40178	0.125566	White	Black

Varieties	Physical properties	Maximum	Minimum	Mean	SD	CV(%)
Gombe	Length (cm)	1.1700	0.7250	0.8932	0.1079	12.0775
	Width (cm)	0.7800	0.5250	0.7016	0.0668	9.5259
	Thickness (cm)	0.8600	0.5150	0.5826	0.0825	14.1566
	Arithmetic mean diameter (cm)	0.8367	0.6403	0.7258	0.0471	6.4901
	Geometric mean diameter (cm)	0.8059	0.6349	0.7112	0.0440	6.1805
	Sphericity	0.9697	0.6888	0.8037	0.0753	9.3669
	Surface area (cm ²)	2.0402	1.2663	1.5951	0.1976	12.3870
	Volume (cm ³)	0.4076	0.1005	0.1603	0.0589	36.7296
	Mass (g)	0.3000	0.1100	0.1916	0.0430	22.4325
	Density (g/cm ³)	1.8905	0.6311	1.2583	0.3085	24.5205
Drum	Length (cm)	1.2800	0.9250	1.1462	0.1040	9.0696
	Width (cm)	0.9550	0.6200	0.8160	0.0868	10.6322
	Thickness (cm)	0.7600	0.5000	0.6090	0.0658	10.8092
	Arithmetic mean diameter (cm)	0.9517	0.7283	0.8571	0.0683	7.9744
	Geometric mean diameter (cm)	0.9233	0.7043	0.8273	0.0675	8.1546
	Sphericity	0.8253	0.6334	0.7238	0.0451	6.2257
	Surface area (cm ²)	2.6780	1.5585	2.1641	0.3476	16.0637

Varieties	Physical properties	Maximum	Minimum	Mean	SD	CV(%)
	Volume (cm ³)	0.3317	0.1436	0.2273	0.0565	24.8628
	Mass (g)	0.4200	0.1900	0.3020	0.0743	24.6127
	Density (g/cm ³)	1.2925	0.4138	0.7677	0.1743	22.6997
Sokoto	Length (cm)	1.7050	1.0100	1.1523	0.1421	12.3336
	Width (cm)	0.9800	0.3200	0.8002	0.1519	18.9803
	Thickness (cm)	0.8400	0.5200	0.6890	0.0790	11.4665
	Arithmetic mean	1.0800	0.6983	0.8805	0.0915	10.3926
	diameter (cm)					
	Geometric mean	1.0002	0.6231	0.8549	0.0955	11.1689
	diameter (cm)					
	Sphericity	0.8516	0.5851	0.7457	0.0747	10.0123
	Surface area (cm ²)	3.1426	1.2199	2.3233	0.4990	21.4779
	Volume (cm ³)	0.3820	0.1339	0.2603	0.0760	29.2089
	Mass (g)	0.4400	0.2500	0.3408	0.0509	14.9360
	Density (g/cm ³)	0.9935	0.4616	0.7555	0.1557	20.6062
<i>Oloyin</i> white	Length (cm)	1.3500	0.1700	1.0256	0.2066	20.1424
	Width (cm)	0.8650	0.3400	0.7520	0.1019	13.5558
	Thickness (cm)	0.6600	0.5150	0.5972	0.0555	9.2920
	Arithmetic mean	0.9350	0.5117	0.7916	0.0815	10.2942
	diameter (cm)					
	Geometric mean	0.8897	0.4226	0.7638	0.0927	12.1332
	diameter (cm)					
	Sphericity	2.4861	0.5468	0.8075	0.3564	44.1412
	Surface area (cm ²)	2.4866	0.5611	1.8586	0.3858	20.7571
	Volume (cm ³)	0.2517	0.1345	0.1887	0.0303	16.0748
	Mass (g)	0.3600	0.2000	0.2532	0.0364	14.3635
	Density (g/cm³)	0.9168	0.5518	0.7428	0.0796	10.7203
<i>Oloyin</i> brown	Length (cm)	1.3500	0.9500	1.1163	0.1194	10.6976
	Width (cm)	0.9700	0.6250	0.8108	0.0956	11.7915
	Thickness (cm)	0.7200	0.4400	0.5619	0.0636	11.3136
	Arithmetic mean	0.9417	0.7167	0.8296	0.0608	7.3320
	diameter (cm)					
	Geometric mean	0.8910	0.6914	0.7952	0.0554	6.9671
	diameter (cm)					
	Sphericity	0.9085	0.6297	0.7171	0.0629	8.7664
	Surface area (cm ²)	2.4939	1.5018	1.9960	0.2787	13.9651
	Volume (cm ³)	0.2969	0.1255	0.1879	0.0424	22.5482
	Mass (g)	0.3600	0.1600	0.2504	0.0436	17.4058
	Density (g/cm ³)	1.0238	0.4364	0.7576	0.1418	18.7138

3.2 Water Uptake Characteristics

Fig. 1 shows the evolution of water uptake isotherms at different temperatures for the five varieties of cowpea; *Gombe, Oloyin* white, Drum, *Oloyin* brown, and *Sokoto*. It was observed that water uptake was faster in the initial stages at all temperatures, especially in the first 30 minutes, and gradually slowed down as the moisture content approached saturation point known as equilibrium moisture content. According to Hsu [24], it had been demonstrated that diffusion in the solid endosperm is the main mechanism that controls the rate of absorption in seeds regardless of the process conditions. There was a noticeable effect of temperature on the grain

moisture, mainly on the dynamic of hydration characteristics and also on the equilibrium moisture of the five varieties.

3.3 Modelling of Absorption Characteristics

The data of gravimeteric based water absorption of five (5) varieties of cowpea at the different soaking temperatures were converted into the moisture content. Then these data were fitted to the selected models which include the Peleg model, page model, kaptso model, Weibul model and first order model (Table 1). The results of nonlinear regression analyses and statistical analyses of the different models including the

constants of the models and the comparison criteria were used to evaluate goodness of fit namely, R^2 , χ^2 , RMSE and SEE. These results are presented in Table 4-8fordescribing water absorption for *Gombe*, *Oloyin* white drum, *Oloyin* brown and *Sokoto* varieties respectively. Base on the criteria of the highest R² and the lowest χ^2 , RMSE and SEE values, the best model for describing the water absorption of the five varieties of cowpea was selected. Statistical

results of semi-theoretical models show that the R², χ 2, RMSE and SEE values varied between 0.9663 and 0.9997, 1.0 x 10⁻⁴ and 4.3 x 10⁻³, 0.0066 and 0.0818, and 0.0004 and 0.1003, respectively. This indicated that some models provided a good representation of the experimental results. However, statistical results show that the Weibull model gave the highestR² in accordance with the lowest vales of χ^2 , RMSE and SEE for all the five varieties at all




Fig. 1. Moisture content vs soaking time at different temperature Table 4. Model parameter for modelling of *Gombe* variety

Temperature	Model	Model constant	Goodness of fit parameter				
			SEE	R ²	RMSE	χ²	
70°C	Peleg	K1 = 6.6249,	0.0049	0.9968	0.0181	0.0004	
	5	K2 = 0.7712					
	Page	K = 0.6877, n = 0.1546,	0.0006	0.9996	0.0065	0.0001	
	0	Me = 139.2172				-	
	Kaptso	K = 0.1491, T = 11.5658,	0.0519	0.9677	0.0588	0.0043	
		Me = 135.9337					
	Weibul	a = 15.0951, b = 0.6877,	0.0006	0.9996	0.0065	0.0001	
		Me = 139.2172					
	First	K = 0.0591,	0.0110	0.9930	0.0270	0.0008	
	order	me = 137.8261					
60°C	Peleg	K1 = 0.8334,	0.0062	0.9928	0.0203	0.0005	
	•	K2 = 1.0371					
	Page	K = 2.154, n = 0.0071,	0.0021	0.9975	0.0119	0.0002	
	J	Me = 109.5936					
	Kaptso	K = 0.2971, T = 6.5901,	0.0021	0.9975	0.0120	0.0002	
		Me = 109.5998					
	Weibul	a = 9.9303, b = 2.163,	0.0021	0.9975	0.0119	0.0002	
		Me = 109.5969					
	First	K = 0.1651,	0.0023	0.9973	0.0124	0.0002	
	order	me = 109.6278					
50°C	Peleg	K1 = 3.2718,	0.0336	0.9709	0.0473	0.0026	
	5	K2 = 0.8934			-	-	
	Page	K = 0.8592, n = 0.1381,	0.0169	0.9854	0.0336	0.0014	
	- 3 -	Me = 123.5391					
	Kaptso	K = 0.2211, T = 9.1316,	0.0236	0.9796	0.0396	0.0020	
	- 1	Me = 122.6927					
	Weibul	a = 10.0097, b = 0.8592,	0.0169	0.9854	0.0336	0.0014	
	-	Me = 123.5391		-			
	First	K = 0.0922,	0.0175	0.9849	0.0341	0.0013	
	order	me = 123.3369					
40°C	Peleg	K1 = 8.6704,	0.0186	0.9898	0.0352	0.0014	
	- 0	K2 = 0.7526					
	Page	K = 0.7407, n = 0.1099,	0.0148	0.9926	0.0314	0.0012	
	0-	Me = 141.166					
	Kaptso	K = 0.1483, T = 11.5312,	0.0520	0.9678	0.0589	0.0043	
	- 1	Me = 136.7293					
	Weibul	a = 15.0322, b = 0.6863,	0.0007	0.9996	0.0066	0.0001	
	'	Me = 140.0151					
	First	K = 0.0593,	0.0112	0.9930	0.0273	0.0009	
	order	me = 138.6096					
30°C	Peleg	K1 = 6.6243,	0.0244	0.9884	0.0403	0.0019	
	- 0	K2 = 0.7712					
	Page	K = 0.6875, n = 0.1546,	0.0178	0.9917	0.0345	0.0015	
	-90	Me = 139.2214	0.0110	0.0011	0.0010	0.0010	
	Kaptso	K = 0.0825, T = 17.3501,	0.0579	0.9692	0.0621	0.0048	
		Me = 139.6012	0.0010	0.0002	0.0021	0.0010	
	Weibul	a = 24.5777, b = 0.8064,	0.0038	0.9979	0.0160	0.0003	
	,, cibui	Me = 142.2912	0.0000	0.0070	0.0100	0.0000	
	Firs	K = 0.0399,	0.0095	0.9948	0.0252	0.0007	
	order	me = 141.1934	0.0000	0.00+0	0.0202	0.0007	
		5. Model parameter for mo	ما ما السعة م		veriet-		

Temperature	Model	Model constant		Statistica	al parameter	
			SEE	R ²	RMSE	χ²
70°C	Peleg	K1 = 2.5325,	0.0093	0.9916	0.0249	0.0007
	Page	K2 = 0.9043 K = 1.2431, n = 0.057,	0.0006	0.9995	0.0064	0.0001
	i age	Me = 123.5988	0.0000	0.3335	0.0004	0.0001
	Kaptso	K = 0.2379,	0.0008	0.9993	0.0072	0.0001
		T = 8.2783,				
	Weibul	Me = 123.4815 a = 10.0053,	0.0006	0.9995	0.0064	0.0001
	Weibui	a = 10.0053, b = 1.2432,	0.0000	0.9995	0.0004	0.0001
		Me = 123.5987				
	First	K = 0.1117,	0.0009	0.9992	0.0076	0.0001
	order	me = 123.7377				
60°C	Peleg	K1 = 0.8294,	0.0048	0.9955	0.0179	0.0004
	Daga	$K_2 = 0.9258$	0.0010	0.0000	0.0094	0.0001
	Page	K = 2.16, n = 0.0071, Me = 122.4769	0.0010	0.9990	0.0084	0.0001
	Kaptso	K = 0.3004,	0.0011	0.9990	0.0084	0.0001
		T = 6.5426,				
		Me = 122.4839				
	Weibul	a = 9.8676,	0.0010	0.9990	0.0084	0.0001
		b = 2.1735,				
	First	Me = 122.4768 K = 0.1671,	0.0012	0.9989	0.0089	0.0001
	order	me = 122.519	0.0012	0.9909	0.0009	0.0001
50°C	Peleg	K1 = 3.5211,	0.0439	0.9724	0.0541	0.0034
	0	K2 = 0.7599				
	Page	K = 0.7923,	0.0219	0.9862	0.0382	0.0018
		n = 0.1502,				
	Kantaa	Me = 143.9786 K = 0.2076,	0.0450	0.9719	0.0548	0.0037
	Kaptso	T = 9.5356,	0.0450	0.9719	0.0546	0.0037
		Me = 142.3389				
	Weibul	a = 10.9378,	0.0219	0.9862	0.0382	0.0018
		b = 0.7923,				
		Me = 143.9785	0.0050	0.00.40	0.0440	0.0040
	First	K = 0.0814,	0.0252	0.9842	0.0410	0.0019
40°C	order Peleg	me = 143.5201 K1 = 7.0208,	0.0506	0.9865	0.0581	0.0039
	i cicy	K2 = 0.6714	0.0000	0.0000	0.0001	0.0000
	Page	K = 0.8471, n = 0.083,	0.0372	0.9942	0.0498	0.0031
	-	Me = 157.7889				
	Kaptso	K = 0.1525,	0.0450	0.9767	0.0548	0.0038
		T = 11.6329, Mo = 149.3876				
	Weibul	Me = 149.3876 a = 15.418,	0.0015	0.9992	0.0100	0.0001
	Vicibul	b = 0.7976,	0.0010	0.0002	0.0100	0.0001
		Me = 152.0426				
	First	K = 0.0606,	0.0061	0.9968	0.0201	0.0005
	order	me = 151.26	0.000-			
30°C	Peleg	K1 = 6.6243,	0.0620	0.9853	0.0643	0.0048
	Page	K2 = 0.7712 K = 0.6875,	0.0407	0.9940	0.0521	0.0034
	Page	n = 0.1546,	0.0407	0.5940	0.0521	0.0034
		Me = 139.2214				
	Kaptso	K = 0.098,	0.0577	0.9770	0.0620	0.0048

Temperature	Model	Model constant	Statistical parameter					
			SEE	R ²	RMSE	χ²		
		T = 15.9966,						
		Me = 161.117						
	Weibul	a = 22.1878, b = 0.9007,	0.0052	0.9978	0.0185	0.0004		
		Me = 163.5391						
	First	K = 0.0444,	0.0067	0.9972	0.0212	0.0005		
	order	me = 163.0231						

Temperature	Model	Model constant		Statistica	l parameter	
•			SEE	R ²	RMSE	χ²
70°C	Peleg	K1 = 2.4364,	0.0037	0.9960	0.0157	0.0003
	-	K2 = 0.9919				
	Page	K = 0.8931,	0.0004	0.9996	0.0051	0.0000
	Ū.	n = 0.163,				
		Me = 112.5775				
	Kaptso	K = 0.254,	0.0012	0.9987	0.0089	0.0001
	•	T = 7.8713,				
		Me = 112.292				
	Weibul	a = 7.6209,	0.0004	0.9996	0.0051	0.0000
		b = 0.8931,				
		Me = 112.5775				
	First	K = 0.1213,	0.0004	0.9995	0.0055	0.0000
	order	me = 112.5042				
60°C	Peleg	K1 = 1.3507,	0.0028	0.9968	0.0136	0.0002
	- 0	K2 = 1.0267				
	Page	K = 2.0938,	0.0007	0.9992	0.0069	0.0001
	- 0 -	n = 0.008,				
		Me = 109.7671				
	Kaptso	K = 0.2899,	0.0007	0.9992	0.0068	0.0001
		T = 6.8337,				
		Me = 109.7784				
	Weibul	a = 6.8302,	0.0007	0.9992	0.0066	0.0001
		b = 1.0722,	0.0001	0.0001	0.0000	
		Me = 109.8274				
	First	K = 0.1551,	0.0007	0.9992	0.0066	0.0001
	order	me = 109.8427	0.0001	0.0002	0.0000	0.0001
50°C	Peleg	K1 = 2.6496,	0.0533	0.9544	0.0596	0.0041
		K2 = 0.8969				
	Page	K = 1.2057,	0.0250	0.9787	0.0408	0.0021
	- 0 -	n = 0.0542,				
		Me = 123.1242				
	Kaptso	K = 0.2244,	0.0261	0.9777	0.0417	0.0022
		T = 9.2603,				
		Me = 122.8658				
	Weibul	a = 11.2171,	0.0250	0.9787	0.0408	0.0021
		b = 1.2058,				
		Me = 123.1242				
	First	K = 0.0972,	0.0257	0.9781	0.0414	0.0020
	order	me = 123.273	0.0201	0.0101		0.0010
40°C	Peleg	K1 = 8.3219,	0.0435	0.9765	0.0539	0.0033
	. 0.09	K2 = 0.7559	0.0100	0.0700	0.0000	0.0000
	Page	K = 0.8452,	0.0237	0.9895	0.0397	0.0020
	i ayu	n = 0.0802,	0.0207	0.0000	0.0007	0.0020
		n = 0.0002,				

Table 6. Model parameter for modelling of Drum variety

Temperature	Model	Model constant		Statistica	parameter	
			SEE	R ²	RMSE	χ²
		Me = 140.0091				
	Kaptso	K = 0.1534,	0.0336	0.9798	0.0473	0.0028
		T = 11.7596,				
		Me = 137.7025				
	Weibul	a = 15.6295,	0.0017	0.9989	0.0107	0.0001
		b = 0.8644,				
		Me = 139.7626				
	First	K = 0.0612,	0.0034	0.9979	0.0152	0.0003
	order	me = 139.3415				
30°C	Peleg	K1 = 6.8988,	0.0376	0.9834	0.0500	0.0029
		K2 = 0.7712				
	Page	K = 0.6875,	0.0240	0.9904	0.0400	0.0020
		n = 0.1546,				
		Me = 139.2214				
	Kaptso	K = 0.0812,	0.0504	0.9730	0.0580	0.0042
		T = 17.7354,				
		Me = 138.2399				
	Weibul	a = 24.9156,	0.0018	0.9990	0.0109	0.0001
		b = 0.8541,				
		Me = 140.4639				
	First	K = 0.0395,	0.0051	0.9972	0.0185	0.0004
	order	me = 139.7282				

Table 7. Model parameter for modelling of Oloyin brown variety

Temperature	Model	Model constant	Statistical parameter				
-			SEE	R²	RMSE	χ²	
70°C	Peleg	K1 = 1.1269, K2 = 1.0681	0.0036	0.9955	0.0155	0.0003	
	Page	K = 5.4884, n = 2397.713, Me = 103.2242	0.0074	0.9908	0.0222	0.0006	
	Kaptso	K = 0.3044, T = 7.0578, Me = 103.8377	0.0007	0.9992	0.0067	0.0001	
	Weibul	a = 13.893, b = 11.3828, Me = 103.8308	0.0007	0.9992	0.0067	0.0001	
	First order	K = 0.1607, me = 103.8791	0.0008	0.9990	0.0072	0.0001	
60°C	Peleg	K1 = 1, K2 = 1.0121	0.0139	0.9845	0.0304	0.0011	
	Page	K = 3.0353, n = 0.0086, Me = 108.5042	0.0054	0.9940	0.0190	0.0004	
	Kaptso	K = 2.4689, T = 0.8901, Me = 108.5042	0.0054	0.9940	0.0190	0.0004	
	Weibul	a = 2.5073, b = 1.8337, Me = 108.5042	0.0054	0.9940	0.0190	0.0004	
	First order	K = 4.7984, me = 108.5042	0.0054	0.9940	0.0190	0.0004	
50°C	Peleg	K1 = 2.8539, K2 = 0.8012	0.0547	0.9623	0.0604	0.0042	
	Page	K = 0.864, n = 0.136, Me = 133.6083	0.0310	0.9786	0.0455	0.0026	
	Kaptso	K = 0.24, T = 9.698, Me = 132.6118	0.0411	0.9718	0.0523	0.0034	
	Weibul	a = 10.0636, b = 0.864, Me = 133.6082	0.0310	0.9786	0.0455	0.0026	
	First order	K = 0.0919, me = 133.3993	0.0318	0.9781	0.0461	0.0024	
40°C	Peleg	K1 = 9.0144, K2 = 0.707	0.0092	0.9968	0.0248	0.0007	
	Page	K = 0.6421, n = 0.1427, Me = 147.2689	0.0103	0.9963	0.0263	0.0009	
	Kaptso	K = 0.1056, T = 14.8035,	0.0884	0.9560	0.0768	0.0074	

Temperature	Model	Model constant		Statistical	parameter	•
			SEE	R ²	RMSE	χ²
		Me = 143.7714				
	Weibul	a = 19.6205, b = 0.6668, Me = 147.9545	0.0060	0.9969	0.0200	0.0005
	First order	K = 0.0475, me = 145.7286	0.0231	0.9881	0.0393	0.0018
30°C	Peleg	K1 = 6.8988, K2 = 0.7712	0.0077	0.9977	0.0226	0.0006
	Page	K = 0.6875, n = 0.1546, Me = 139.2214	0.0119	0.9954	0.0282	0.0010
	Kaptso	K = 0.0919, T = 16.0945, Me = 141.5887	0.1003	0.9491	0.0818	0.0084
	Weibul	a = 22.0161, b = 0.6199, Me = 146.6721	0.0076	0.9960	0.0224	0.0006
	First order	K = 0.0432, me = 143.4818	0.0322	0.9833	0.0463	0.0025

Table 8. Model parameter for modelling of Sokoto variety
--

Temperature	Model	Model constant		Statistica	l paramete	ər
•			SEE	R ²	RMSE	χ²
70°C	Peleg	K1 = 1.3074, K2 = 1.0034	0.0132	0.9856	0.0297	0.0010
	Page	K = 3.0353, n = 0.0086,	0.0197	0.9785	0.0363	0.0016
		Me = 110.444				
	Kaptso	K = 2.3947, T = 0.8633,	0.0197	0.9785	0.0363	0.0016
		Me = 110.444				
	Weibul	a = 2.5073, b = 1.8337,	0.0197	0.9785	0.0363	0.0016
		Me = 110.444				
	First order	K = 4.7984, me = 110.444	0.0197	0.9785	0.0363	0.0015
60°C	Peleg	K1 = 0.8442, K2 = 0.9642	0.0072	0.9928	0.0219	0.0006
	Page	K = 3.0353, n = 0.0086,	0.0105	0.9895	0.0264	0.0009
		Me = 114.9667				
	Kaptso	K = 2.4207, T = 0.8727,	0.0105	0.9895	0.0264	0.0009
		Me = 114.9667				
	Weibul	a = 2.5073, b = 1.8337,	0.0105	0.9895	0.0264	0.0009
		Me = 114.9667	0.0405	0 0005		
		K = 4.7984, me = 114.9667	0.0105	0.9895	0.0264	0.0008
50°C	Peleg	K1 = 2.3926, K2 = 0.8672	0.0416	0.9663	0.0527	0.0032
	Page	K = 1.0023, n = 0.1021,	0.0209	0.9831	0.0373	0.0017
	Kantaa	Me = 126.1313	0.0005	0.0040	0 0000	0 0000
	Kaptso	K = 0.2413, T = 9.0303,	0.0235	0.9810	0.0396	0.0020
		Me = 125.6975	0 0000	0.0004	0 0 2 7 2	0 0017
	Weibul	a = 9.74, b = 1.0023, Me = 126.1313	0.0209	0.9831	0.0373	0.0017
	Eirct ordor	K = 0.1028, me = 126.1334	0.0209	0.9831	0.0373	0.0016
40°C	Peleg	K = 0.1028, me = 120.1334 K1 = 6.1186, K2 = 0.7297	0.0209	0.9661	0.0651	0.0010
	Page	K = 0.8144, n = 0.1039,	0.0030	0.9828	0.0051	0.0049
	Faye	$M = 0.0144, \Pi = 0.1039,$ Me = 144.7903	0.0370	0.9020	0.0497	0.0031
	Kaptso	K = 0.1956, T = 10.6706,	0.0354	0.9781	0.0486	0.0029
	Rapiso	Me = 138.8383	0.0004	0.5701	0.0400	0.0023
	Weibul	a = 12.9528, b = 0.865,	0.0136	0.9915	0.0301	0.0011
	Vicioai	Me = 140.5344	0.0100	0.0010	0.0001	0.0011
	First order		0.0150	0.9907	0.0316	0.0012
30°C	Peleg	K1 = 6.8988, K2 = 0.7712	0.0371	0.9862	0.0498	0.0029
	Page	K = 0.6875, n = 0.1546,	0.0261	0.9913	0.0417	0.0022
	. 490	Me = 139.2214	5.0201	5.00.0	5.0117	0.0022
	Kaptso	K = 0.1009. T = 14.9642	0.0681	0.9669	0.0674	0.0057
	Kaptso	K = 0.1009, T = 14.9642, Me = 146.7307	0.0681	0.9669	0.0674	0.0057

Femperature	Model	Model constant		Statistical parameter				
				SEE	R ²	RMSE	χ²	
		Me = 14	9.4733					
	First order	K = 0.04	177, me = 148.3	3688	0.0092	0.9954	0.0248	0.0007
		_		• . •				
Ta	ble 9. Therm	odynam	ic parameters	of the	hydratio	on of Gomb	e variety	
Varieties	Temperat	ure (K)	Ea (kJ/mol)	∆ H (c	al/mol)	ΔS (cal/km	nol) ∆G (l	kcal/mol
Gombe	343		38.51	-2813	3.2	-230.46	76.23	3
	333		39.28	-2729	.28	-236.04	75.87	7
	323		40.34	-2645	5.08	-236.28	73.67	7
	313		43.21	-2559	.07	-220.71	66.52	2
	303		49.94	-2469	.2	-212.27	61.85	5
Oloyin white	343		25.67	-2826	6.03	-220.14	72.68	3
	333		49.43	-2719	.14	-210.58	67.4	
	323		40.44	-2644	.98	-217.75	67.69	9
	313		44.45	-2557	.83	-218.83	65.94	1
	303		41.79	-2477	.35	-213.93	62.34	4
Drum	343		25.16	-2826	6.54	-219.73	72.54	1
	333		40.68	-2727	.89	-213.82	68.47	7
	323		40.44	-2644	.98	-215.39	66.92	2
	313		48.45	-2553	.83	-219.85	66.26	3
	303		42.65	-2476	6.49	-214.1	62.39	9
Oloyin brown	343		36.37	-2815	5.33	-215.34	71.05	5
	333		45.73	-2722	.83	-211.79	67.8	
	323		40.44	-2644	.98	-216	67.12	2
	313		50.21	-2552	2.07	-220.34	66.4 <i>°</i>	1
	303		42.66	-2476	6.49	-214.09	62.39	9
Sokoto	343		33.78	-2817	.92	-216.11	71.3 <i>′</i>	1
	333		48.9	-2719	.66	-210.68	67.44	4
	323		40.44	-2644	.98	-214.54	66.65	5
	313		32.52	-2569	.77	-218.87	65.94	4
	303		42.66	-2476	6.49	-214.09	62.39	9

temperature. Therefore, the Weibull model was considered the best model for describing both the water absorption of cowpea during soaking within the experimental range of study disagree with the findings of [36] who suggested Page model has the best model for describing the soaking behaviour of white rice, and [37] at room temperature claims to investigate the effect of soaking temperature on the constant and coefficient values of the Page model, namely, k and n, However, the variation in this result can be attribute to the class of the seed, which might directly affect the performance of the model. Nevertheless, the Weibull model can be used to estimate with great accuracy of the moisture content of the selected cowpea at any time during the soaking process.

3.4 Thermodynamic Approach

Arrhenius equation was used for the evaluation of the temperature dependence of K_1 in peleg model. The activation energy is a function of

temperature and therefore represents the influence of temperature on K₁. Table 9shows the activation energy obtained by nonlinear regression of K₁ as an exponential function of inverse temperature. The average values of Ea obtained for the five varieties of cowpea; *Gombe, Oloyin* white, Drum, *Oloyin* brown and *Sokoto* varieties are 42.26 ± 4.65, 40.36 ±8.90, 39.47 ±8.62, 43.08 ±5.25 and 39.66 ±6.72 respectively. The lower value of Ea and the negatives values of entropy indicate that the seeds were more thermally stable and hydration changes was less influenced by temperature [38].

The values of enthalpy (ΔH^*) in Table 9 were negative at all temperature and varieties, indicating that cowpea hydration is associated with exothermic (energetically favourable) transformations. The values of enthalpy vary from one variety to the other. The negative values of enthalpy in the hydration was also verified [38] for Bambara seeds and [39] for barley. Gibbs free energy is the driving force at constant temperature and pressure. Changes in free energy are generally coupled with enthalpy and entropy changes. The sign of ΔG informs about the spontaneity of the reaction. If $\Delta G < 0$, the reaction is spontaneous [40]. In this study, positive values of ΔG were obtained, showing that the process was not spontaneous. A noticeable difference was found in ΔG for all the varieties at different temperatures. The ΔG^* decreased with increasing temperature was observed, indicating that hydration was influenced by temperature.

4. CONCLUSION

The following information were drawn based on the finding of the study of hydration characteristics of five different varieties of cowpea as function of temperature;

- The initial moisture content of the saturated cowpea was estimated as 13.56 ±1.15, 15.05 ±2.27, 13.30 ±0.37, 10.85 ±0.13, 12.40 ±0.13 for Gombe, Oloyin white, Drum, Oloyin brown and Sokoto varieties respectively.
- 2. The weight of the seed was measured as 0.19 ± 0.04 , 0.30 ± 0.07 , 0.34 ± 0.05 , 0.25 ± 0.04 and $0.25 \pm 0.04g$ for *Gombe*, Drum, *Sokoto*, *Oloyin* white, and *Oloyin* brown respectively.
- 3. The length (L), width (W), and thickness (T) was measured as 0.89 ± 0.11 , 0.70 ± 0.07 and 0.58 ± 0.08 respectively for *Gombe* variety; 1.15 ± 0.10 , 0.82 ± 0.09 and 0.61 ± 0.07 for Drum variety respectively, 1.15 ± 0.14 , 0.8 ± 0.15 and 0.68 ± 0.07 for *Sokoto* variety respectively, 1.02 ± 0.21 , 0.75 ± 0.10 and 0.60 ± 0.06 for *Oloyin* white variety respectively and 1.12 ± 0.12 , 0.81 ± 0 ;10 and 0.56 ± 0.06 for *Oloyin* brown respectively.
- The water uptake of the cowpea was faster at the initial stage and gradually slow down until the equilibrium moisture content is attained for all the varieties.
- Weibull model was adjudged as the best fitted model for describing the water absorption property of all the selected varieties of the cowpea.
- The Activation energy of the selected five varieties of cowpea; *Gombe, Oloyin* white, Drum, *Oloyin* brown and *Sokoto* varieties are 42.26 ± 4.65, 40.36 ± 8.90, 39.47 ± 8.62, 43.08 ± 5.25 and 39.66 ± 6.72 respectively and drum varieties will be

more stable during processing as it has the lowest Activation energy of 39.47 ± 8.62 .

7. The information provided on the physical property can be used to facilitate the design of handling and processing equipment for the selected cowpea.

COMPETING INTERESTS

Authors have declared that no competing interests exist.

REFERENCES

- Sobukola OP, Abayomi HT. Physical properties and rehydration characteristics of different varieties of maize (*Zea mays* L.) and cowpea (*Vigna unguiculata* L. Walp) seeds. J. Food Process. Pres. 2011;35:299.
- Kaptso KG, Njintang YN, Komnek AE, Hounhouigan J, Scher J, Mbofung CMF. Physical properties and rehydration kinetics of two varieties of cowpea (*Vigna unguiculata*) and Bambara groundnuts (Voandzeia subterranea) seeds. J. Food Eng. 2008;86:91.
- Nwokolo EA. The need to increase consumption of pulses in the developing world. In: Nwokolo EA, Smart J, Food and Feed from Legumes and Oil Seeds. Chapman and Hall, London; 1996.
- Rachie KO. Highlight of grain legume improvement at IITA 1970–73. Proceedings of the First IITA Grain Legume Improvement Workshop 29 October – 2 November, Ibadan. Nigeria; 1973.
- Fasoyiro SB, Ajibade SR, Omole AJ, Adeniyan ON, Farinde EO. Proximate, mineral and antinutritional factors of some underutilized grain legumes in south western Nigeria. Nutrition Food Sciences. 2006;36:18-23.
- Drumm TD, Gray JI, Hosfield GL, Uebersax MA. Lipid, saccharide, protein, phenolic acid and saponin contents of four market classes of edible dry beans as influenced by soaking and canning. J Sci Food Agric. 1990;51:425-35.
- Carmona-Garcia R, Osorio-Diaz P, Agama-Acevedo E, Tovar J, Bello-Perez LA. Composition and effect of soaking on starch digestibility of *Phaseolus vulgaris* (L.) cv. Mayocoba. Intl J Food Sci Technol. 2007;42:296–302.

- Huma N, Anjum M, Sehar S, Khan MI, Hussain S. Effect of soaking and cooking on nutritional quality and safety of legumes. Nutr Food Sci. 2008;38:570–7.
- Yasmin A, Zeb A, Khalil AW, Paracha GMu-D, Khattak AB. Effect of processing on anti-nutritional factors of red kidney bean (*Phaseolus vulgaris*) grains. Food Bioprocess Tech. 2008;1:415–9.
- Bordin LC, Coelho CMM, Souza CAd, Zilio M. Diversidadegenetica para a padronizacao do tempo e percentual de hidratacao preliminarao teste ~de coccao de graos de feij ao. Food Sci Tech-Brazil. 2010;30:890–6.
- 11. Silva CAB, Bates RP, Deng JC. Influence of soaking and cooking upon the softening and eating quality of black beans (*Phaseolus vulgaris*). J Food Sci. 1981;46: 17:16–20.
- Martinez-Manrique E, Jacinto-Hernandez C, Garza-Garcia R, Campos A, Moreno E, Bernal-Lugo I. Enzymatic changes in pectic polysaccharides related to the beneficial effect of soaking on bean cooking time. J Sci Food Agric. 2011;91: 2394–8.
- Wood JA. Evaluation of cooking time in pulses: A review. Cereal Chem. 2016;94: 32–48.
- 14. Sefa-Dedeh S, Stanley DW. The Relationship of microstructure of cowpeas to water absorption and dehulling properties. Cereal Chem. 1979;56 (4): 379-386.
- Wang N, Hatcher DW, Toews R, Gawalko EJ. Influence of cooking and dehulling on nutritional composition of several varieties of lentils (*Lens culinaris*). LWT – Food Sci Technol. 2009;42:842–48.
- Singh N, Eckhoff S. Wet milling of corn-A review of laboratory-scale and pilot plantscale procedures. Cereal Chem. 1996;73: 659–67.
- Carvajal-Larenas FE, Nout MJR, van Boekel MAJS, Koziol M, Linnemann AR. Modelling of the aqueous debittering process of *Lupinus mutabilis* sweet. LWT – Food Sci Technol. 2013;53:507-16.
- Abd EL-Hady EA, Habiba RA. Effect of soaking and extrusion conditions on antinutrients and protein digestibility of legume seeds. Food Science and Tech. 2003;36:285-293.
- 19. Miano AC, Augusto PED. From the sigmoidal to the downward concave shape behavior during the hydration of grains:

Effect of the initial moisture content on adzuki beans (*Vigna angularis*). Food Bioprod Process. 2015;96:43–51.

- 20. Peleg M. An empirical model for the description of moisture sorption curves. Journal of Food Science. 1988;53:1216-1219.
- 21. Piergiovanni AR. Kinetic of water adsorption in common bean considerations on the suitability of Peleg's model for describing bean hydration. J Food Process Pres. 2011;35:447-52.
- 22. Piergiovanni AR, Sparvoli F, Zaccardelli M. 'Fagiolo a Formella', an Italian lima bean ecotype: Biochemical and nutritional characterisation of dry and processed seeds. J Sci Food Agric. 2012;92:2387-93.
- 23. Oliveira AL, Colnaghi BG, Silva EZ, Gouvea IR, Vieira RL, Augusto PED. Modelling the effect of temperature on the hydration kinetic of adzuki beans (*Vigna angularis*). J Food Eng. 2013;118:417-20.
- 24. Hsu KH. A diffusion model with a concentration-dependent diffusion coefficient for describing water movement in legumes during soaking. Journal of Food Science. 1983;48(2):618-622. Available:http://dx.doi.org/10.1111/j.1365-2621.1983.tb10803.x
- Addo A, Bart-Plange A, Dzisi K. Water absorption characteristics of Obatanpa and Mamabahybrids of maize (*Zea mays*). Int. J. Food Eng.; 2006. Available:http://www.bepress.com/ijfe/vol2/ iss3/art7.h
- 26. Calzetta-Resio A, Aguerre RJ, Suarez C. Hydration kinetics of amaranth grain. Journal of Food Engineering. 2006;72: 247-253.
- 27. Baryeh EA. Physical properties of millet. J Food Eng. 2002;51:39–46. DOI: 10.1016/S0260-8774(01)00035-8
- Maharaj V, Sankat CK. The rehydration characteristics and quality of dehydrated dasheen leaves. Canadian Agricultural Engineering. 2000;42(2):81-85.
- 29. Seyhan-Gurtas F, Ak MM, Evranuz EO. Water diffusion coeffcients of selected legumes grown in Turkey as affected by temperature and variety. Turkish Journal of Agriculture. 2001;25(5):297-304.
- Tagawa A, Muramatsu Y, Nagasuna T, Yano A, limoto M, Murata S. Water absorption characteristics of wheat and barley during soaking. Transactions of the American Society of Agricultural Engineers. 2003;46(2):361-366.

- Ghafoor M, Misra NN, Mahadevan K, Tiwari BK. Ultrasound assisted hydration of navy beans (*Phaseolus vulgaris*). Ultrason Sonochem. 2014;21:409-414.
- 32. Shafaei SM, Masoumi AA. Evaluation of physical properties and hydration kinetics of red lentil (*Lens culinaris*) at different processed levels and soaking temperatures. Agricultural Communications. 2014;2(2):15-21.
- Zura L, Uribe E, Lemus-Mondaca R, Saavedra-Torrico J, Vega-Gálvez A, Di Scala K. Rehydration capacity of Chilean papaya (*Vasconcellea pubescens*): Effect of process temperature on kinetic parameters and functional properties. Food Bioprocess Technol. 2013;6:844-850.
- Olapade AA, Okafor GI, Ozumba AU. Olatunji O. Characterization of common Nigerian cowpea (*Vigna unguiculata* L. Walp) varieties. Journal of Food Engineering. 2002;55(2):101-105. Available:http://dx.doi.org/10.1016/S0260-8774(02)00022-5
- 35. Baryeh EA. Physical properties of bambara groundnuts. J. Food Eng. 2001;47:321.
- 36. Kashaninejad M, Maghsoudlou Y, Rafiee S, Khomeir M. Study of hydration kinetics

and density changes of rice (Tarom Mahali) during hydrothermal processing. Journal of Food Engineering. 2007;79: 1383-1390.

- Yadav BK, Jindal VK. Modeling varietal effect on the water uptake behaviour of milled rice (*Oryza sativa* I.) during soaking. Journal of Food Process Engineering. 2007;30(6):670-684. Available:https://doi.org/10.1111/j.1745-4530.2007.00129.x
- Jideani VA, Mpotokwana SM. Modeling of water absorption of Botswana bambara varieties using Peleg's equation. Journal of Food Engineering. 2009;92(2):182-188. Available:http://dx.doi.org/10.1016/j.jfoode ng.2008.10.040
- Montanuci FD, Jorge LMM, Jorge RMM. Kinetic, thermodynamic properties and optimization of barley hydration. Food Science and Technology Campinas. 2013;33(4):690-698.
- Oulahna D, Hebrard A, Cuq B, Abecassis J, Fages J. Agglomeration of durum wheat semolina: Thermodynamic approaches for hydration properties measurements. J. Food Eng. 2012;109(3):619–626.

© 2019 J. Isa et al.; This is an Open Access article distributed under the terms of the Creative Commons Attribution License (http://creativecommons.org/licenses/by/4.0), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Peer-review history: The peer review history for this paper can be accessed here: http://www.sdiarticle3.com/review-history/48388